

## CALCIUM, GEL CALCIUM & CHASSIS GREASE

---

### DESCRIPTION

**CALCIUM/GEL CALCIUM/CHASSIS** grease is manufactured from selected quality base oils, calcium soap and additives to provide excellent water resistance properties and good corrosion and rest protection.

### APPLICATION

- The recommended temperature range of this product is 60°C in continuous service and 90°C for short exposure.
- Water environments such as slips ways and water pump bearings, Nipples, spring leaves, chain Brives, Open and Semi-open Gear Systems.

### BENEFITS

- Excellent water resistance properties
- Good rust and corrosion protection
- Excellent film strength

### PROPERTIES

NLGI	CALCIUM-3	GEL CALCIUM-3	CHASSIS-1
Soap Type	Calcium	Gel Calcium	Calcium
Appearance	Light Brown	Light Brown	Dark Green
Drop Point, °C	98	104	90-95
Worked Penetration	220-250	220-250	310-340
Operating Range	-10 to 80	-10 to 90	-10-90

### POWERMAXX LUBE INDIA

Website: [www.powermaxxlube.com](http://www.powermaxxlube.com) Email: [info.powermaxx918@gmail.com](mailto:info.powermaxx918@gmail.com), [info@powermaxxlube.com](mailto:info@powermaxxlube.com)

CONTACT NUMBER: 996748763, 7506973307