

GEARTECH EP (INDUSTRIAL GEAR OIL)

DESCRIPTION:

GEARTECH EP is high performance gear oil formulated with high viscosity index mineral base oil quality, Sulphur-phosphorus type extreme pressure additives, developed for especially all kinds of steel gears, wind turbines and various types of industrial heavy loaded gearboxes and worm wheel boxes operating under normal to extremely heavy duty conditions. It provides superior resistance against micropitting fatigue. It has improved thermal and oxidation stability over conventional industrial gear oils. It has good demulsibility characteristics, low foaming tendency and provides rust and corrosion protection, wear protection to metal surfaces. It has excellent compatibility with ferrous and non-ferrous metals even at elevated temperatures. **GEARTECH EP** has low friction coefficient and good low-temperature performance, which makes it ideal for wind turbine and other remote, long-life applications.

PERFORMANCE SPECIFICATIONS Meets & exceeds the performance requirements:

Siemens MD revision 15 for Flender gear units, U.S. Steel 224 (AIST 224), AGMA 9005-F16 Antiscuff, DIN 51517, part III (2014), FAG FE-8 as per DIN 51819-3, David Brown S1.53.101 E, ISO 12925-1 (CKD) – 2002.

APPLICATION:

- Recommended for Wind turbine gear drives, power generation, Industrial gear drives & gearboxes especially for heavy loads and high shock loaded gear units such as Sugar Mill, cement industries, paper, steel etc. of all sizes and capacities, remotely located units and extreme high & low temperature environments, where maintenance is infrequent and access can be difficult.
- Recommended for gear boxes using forced circulation or splash, oil bath lubrication.
- Recommended for the lubrication of helical, bevel and planetary type of gear units.

FEATURES & BENEFITS:

- Consistently strong micropitting performance as specified by Flender AG at 60°C and 90°C
- Outstanding demulsibility ensures easy separation from water
- Excellent phosphorus retention ensuring extended wear protection.
- Clean gear performance under conditions of high temperature and oxidation
- Offers excellent corrosion and foam performance.
- Outstanding high load carrying ability.

PROPERTIES

ISO GRADE	68	150	220	320	460	680
Viscosity @ 40°C Cst	68	150	220	320	460	680
Viscosity @ 100°C Cst	8.7	15	19.4	25	30.8	38
Viscosity Index	99	100	100	100	97	92
Pour Point	-24	-24	-19	-15	-12	-9
Flash Point °C	236	240	243	256	262	272
Density 15°C	0.887	0.897	0.905	0.917	0.920	0.924
Foam Tendency, SEQ-I	10/0	10/0	10/0	10/0	10/0	10/0
Copper Strip Corrosion @ 100 °C for 24 hrs.	1b	1b	1b	1b	1b	1b
Rust Protection Sea Water	Pass	Pass	Pass	Pass	Pass	Pass
Total Acid Number, mg KOH/g	0.9	0.9	0.9	0.9	0.9	0.9

POWERMAXX LUBE INDIA

Website: www.powermaxxlube.com Email: info.powermaxx918@gmail.com, info@powermaxxlube.com

CONTACT NUMBER: 996748763, 7506973307