

## ALX HTXX-2 & 0 HD GREASE (Aluminum-Complex)

### DESCRIPTION

**ALX HTXX-2 & 0 HD** grease is a premium high quality temperatures grease formulated with extreme pressure (EP), anti-wear package, fortified with synergistic combination with powerful balanced blend of Aluminum-Complex and special white solid lubricants in a heavy duty chemistry provides thicker and stronger film stability, where bearings are exposed to high shock loads and heavy vibration, high temperature & low speed both exist in indoors and outdoors in both cold and high temperature applications and gives high protection by minimizing metal-to-metal contact and reduces friction, wear at minimal consumption. All of this turn reduces maintenance cost and extend the life of equipment and friction elements avoiding seizure & expensive repairs. This product has been developed to withstand extremely heavy load, slow moving, large open gear drives operating in very hostile environments. Due to its high solid content and Aluminum-Complex thickener it will not slide down the shank of the tool during its operation.

### FEATURES /BENEFITS

- Good water, heat resistance and are not affected by mild acids / alkalis.
- Good corrosion protection and oxidation stability with high drop point.
- Excellent flow and pump-ability for automatic centralized and Individualized systems.
- Thermally stable, can withstand high shock loads, and minimizing metal to metal contact.
- High drop point ensures extended operating temperature range upto -20°C to 180°C.
- Good low temperature pump ability, Good wear protection and Long lasting lubrication.
- You can work with your breaker for long, continuous periods, even in warmer climates.
- Low consumption, Immediate monetary savings, extends bearings life and gives longer relubrication intervals. High protection against seizure and wear, avoiding expensive repairs.

### APPLICATIONS

- **ALX HTXX-2 & 0 HD** has been designed to lubricate: - Journal, Roller & Sleeve bearings, Transmission brasses, Crown wheels, Transmissions open gears, Crystallizer transmission gears & Rotating dryer gears with the capability to resist the permanent attack of pollutants as steam vapour, water, juice and trash.
- **Application Industry:** Sugar mills large heavy loaded in roller journal bearings & large girth gear drives, Steel, Paper, Mining, Cement, Chemical, Marine & Offshore.
- **ALX HTXX-2 & 0 HD** can be applied by high pressure spray systems but, immersion or circulation lubrication is possible too. It is suggested for heavy duty gear drives working at low speeds. This range is strongly recommended in Sugar, cement, mining, chemical and power plants.

### PROPERTIES

SPECIFICATIONS	ALX HTXX-2 460 HD	ALX HTXX-2 680 HD	ALX HTXX-0 1000 HD	ALX HTXX-0 1500 HD	ALX HTXX-0 2000 HD
NLGI Grade available	00, 0, 1, 2				
Colour & Appearance	Beige Brown, Smooth & buttery				
Thickener Soap	Aluminum-Complex				
Viscosity @ 40°C, Cst	460	680	1000	1500	2000
Work Penetration	265-295	265-295	265-295	265-295	265-295
Drop Point	+230	+230	+230	+230	+230
Service Temperature	-20°C to 180°C				
Weld Load	+500	+500	+620	+800	+800

### POWERMAXX LUBE INDIA

Website: [www.powermaxxlube.com](http://www.powermaxxlube.com) Email: [info.powermaxx918@gmail.com](mailto:info.powermaxx918@gmail.com), [info@powermaxxlube.com](mailto:info@powermaxxlube.com)

Contact Number: 996748763, 7506973307