

SEACURE SP CI4 PLUS 15W40 (Marine High Speed Engine Oil)

Seacure SP Ci-4+ 15w-40 for Marine High Speed Engine Oil

DESCRIPTION

SEACURE SP CI-4 PLUS 15W-40 is a mineral based marine engine oil providing good performance in high output, high speed, turbo charged engines operating under severe conditions and has excellent thermo-oxidative stability, controlling deposits and viscosity increase. Excellent soot handling controls soot induced oil thickening and effectively prevents wear. It reduces piston deposits, protects against "Bore Polishing", reduces oil consumption and allows extended drain intervals.

APPLICATIONS

- Turbocharged main and auxiliary engines of all types and all ratings running on Intermediate Fuel oil or on Heavy Fuel oil with high Sulphur content.
- General lubrication of ship board equipment where API: CI4 PLUS quality oils are adequate.
- Recommended for high speed diesel engine in marine, power generation and industrial application on residual fuels.
- SEACURE SP CI-4 PLUS 15W-40 has been formulated with carefully selected additives in mineral base stocks, to provide excellent detergency, dispersancy and anti-wear performance

BENEFITS

- Excellent thermal oxidation stability
- Reducing built up of soot & black sludge.
- Extended oil life, Good wear protection
- Very good oil film strength at extreme pressures.
- Very good detergent properties at high temperatures.
- Very good dispersant properties at low temperatures.
- Excellent capacity for centrifuging and for separating out water and insoluble.
- Very good neutralizing capability of acidic products of combustion.

PROPERTIES

SAE GRADE	SEACURE SP CI-4+ 15W-40
Density,@15°C	0.884
Viscosity @100°C	14.5
Viscosity @40°C	108
Viscosity Index	135
Flash Point	230
Pour Point °C	-27
TBN	10.2